



PMD-326C CD / Media Player

Key Features:

- Plays CD and MP3 files
- Super-fast loading, slot-in CD mechanism
- Random, repeat and power-on-play playback modes
- Supports removable USB thumb drive
- 3.5mm AUX input for playback of other audio devices
- 10-key direct track access buttons
- IR remote included
- Balanced XLR and unbalanced RCA line outputs

Overview:

The PMD-326C is a high-performance professional CD player with USB and 3.5mm AUX inputs designed for the commercial installation market. The PMD-326C has features normally found on higher-priced players, such as Front Panel Lock, Power On Play, direct access to tracks, memory of settings after loss of power, and balanced XLR output. This player is perfect for retail, education, and hotel/conference applications.

Specifications:

- Playable Formats / File Systems
 - CD: CD-DA (CD-TEXT), CD-ROM (ISO9660), CD-R, MP3-CD
 - USB: FAT16 / FAT32
- MP3 Format Supported
 - Extension: MP3
 - Bitrate: 32 to 320 kbps and VBR
 - Sampling Frequency: 44.1 kHz/16-bit
- Number of Channels: 2 (stereo), 1 (mono)
- Frequency Response: 20 Hz–20kHz (\pm 1.0dB)
- S/N Ratio: > 95 dB (A-Weighted)
- Total Harmonic Distortion (THD): < 0.01%
- Dynamic Range: > 85 dB
- Channel Separation: > 80 dB
- Output
 - Balanced XLR
 - Unbalanced RCA
 - Maximum output level: 3 Vrms
- Input
 - Aux in: TRS (3.5mm)
 - Input impedance: Over 10k ohms
 - Maximum input level: 1 Vrms
- USB Thumbdrive Specs
 - Max storage capacity: Up to 32 GB
 - Max file size: 2 GB
- Power Supply
 - USA & Canada: AC 120V, 60 Hz
 - EU, UK, APAC: AC 230V, 50/60 Hz
 - Japan: AC 100V, 50/60 Hz
- Power consumption: 30W
- Operating Environment
 - Operating temperature: 5-35 degrees Celcius (41-95 degrees Fahrenheit)
 - Operating humidity: 25-85%, no condensation
- Dimensions
 - 19.00" x 13.66" x 1.73" / 483 x 347 x 44 mm (with rack ears)

- 17.09" x 13.66" x 1.73" / 434 x 347 x 44 mm (without rack ears)
- Weight: 7.94 lbs. / 3.6 kg